

## MOLYKOTE® MKL-N DISPERSION

### Mineral oil grease with solid lubricants dispersed in solvent

#### FEATURES

- ◆ Penetration
- ◆ Adhesion
- ◆ Protection against wear
- ◆ Corrosion protection
- ◆ Ageing stability

#### COMPOSITION

- ◆ Mineral oil
- ◆ Inhibitors
- ◆ Adhesion improver
- ◆ Solid lubricants
- ◆ Solvents

#### APPLICATION

- ◆ Used for lubrication of chains.

#### TYPICAL PROPERTIES

Specifications writers: These values are not intended for use in preparing specifications. Please contact Dow Corning GmbH, Wiesbaden, Germany before writing specifications on this product.

Standard*	Test	Units	Result
	Colour		Black
	<b>Density</b>		
	Density at 20°C	g/ml	0.87
	<b>Load-carrying capacity, wear protection</b>		
	Four-ball tester (VKA)		
DIN 51 350 pt.4	Weld load	N	1200
DIN 51 350 pt.5	Wear scar under 800N load	mm	0.9
	<b>Corrosion protection</b>		
DIN 51 802	SKF-Emcor method		
	Degree of corrosion		0-1

\* DIN: Deutsche Industrie Norm

#### HOW TO USE

##### How to apply

Apply thinly to clean, dry surfaces using a brush. Small chains can also be dipped. The chain can be used after evaporation of the solvent (approx. 30 minutes).

#### HANDLING PRECAUTIONS

A Product Safety Data Sheet should be obtained from your nearest Dow Corning sales office prior to use.

ATTENTION: Before handling, read product information, Product Safety Data Sheets and container labels for safe use, and any physical and/or health hazard information.

#### USABLE LIFE AND STORAGE

When stored at or below 20°C in the original unopened containers this product has a usable life of 36 months

from the date of production.

Dow Corning will guarantee the usable life of this product until the date indicated on the packaging. This date is shown by the letters "EXP" (meaning Expiry) followed by 4 digits, which stand for the month (last day) and year. Example: "EXP 03/99" means use by 31 March 1999.

#### PACKAGING INFORMATION

This product is available in different standard container sizes. Detailed container size information should be obtained from your nearest Dow Corning sales office or Dow Corning distributor.

#### LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

## HEALTH AND ENVIRONMENTAL INFORMATION

Dow Corning's Health, Environment and Regulatory Affairs (HERA) Department is available to support customers for their product safety needs. For further information, you can contact this group at:

Dow Corning Europe  
HERA Department  
Rue Général de Gaulle, 62  
B-1310 La Hulpe  
Belgium  
TEL:  
Int +32 (0)2 655 2523  
Int +32 (0)2 655 2304  
FAX:  
Int +32 (0)2 655 2013

---

The information contained herein is offered in good faith based on Dow Corning's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that Dow Corning's products are fully satisfactory for your specific applications. Dow Corning's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. UNLESS DOW CORNING PROVIDES YOU WITH A SPECIFIC, DULY SIGNED ENDORSEMENT OF FITNESS FOR USE, DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. SUGGESTIONS OF USE SHALL NOT BE TAKEN AS INDUCEMENTS TO INFRINGE ANY PATENT.

---

**UNITED KINGDOM, NORDIC COUNTRIES, BENELUX, SOUTH AFRICA, EIRE & MIDDLE EAST**  
Dow Corning  
UNITED KINGDOM  
Tel: INT + 44 (0)1 676 52 80 00  
Fax: INT + 44 (0)1 676 52 80 01

**AUSTRIA, GERMANY, SWITZERLAND & EASTERN EUROPE**  
Dow Corning GmbH  
GERMANY  
Tel: INT + 49 (0)611 - 23 71  
Fax: INT + 49 (0)611 - 237 610

**ITALY & EASTERN MEDITERRANEAN COUNTRIES**  
Dow Corning S.p.A.  
ITALY  
Tel: INT + 39 039 - 60 711  
Fax: INT + 39 039 - 68 99 660

**POLAND**  
Dow Corning Polska Sp. z o.o.  
Tel: INT + 48 (0)22 645 14 45  
Fax: INT + 48 (0)22 645 14 40

**SPAIN & PORTUGAL**  
Dow Corning Ibérica S.A.  
SPAIN  
Tel: INT + 34 (0)93 - 405 12 15  
Fax: INT + 34 (0)93 - 405 38 94

**FRANCE & NORTH AFRICA**  
Dow Corning France S.A.  
FRANCE  
Tel: INT + 33 (0)4 72 84 13 60  
Fax: INT + 33 (0)4 72 84 13 79

**R  
12/98**